















Roof products

SEALING - REPAIRING - RENOVATE - PROTECTING









Paraphalt Liquid

Semi-liquid coating for waterproofing and renovation of roofs and guttering. Sealing, protection, renovation and maintenance of roofing, zinc, asbestos cement and corrugated plates.

Packing: 1 kg, 5 kg, 10 kg & 25 kg Colour: black

Paraphalt Reflex

Liquid bitumen paint with aluminium particles which form a reflective silvercoloured, UV-resistant topcoat. Protects against accelerated ageing, corrosion and slows moss formation. Forms a thermal shield and stops the formation of cracks in the roofina.

Packing: 1 kg, 5 kg, 10 kg & 25 kg **Colour:** silver

Paraphalt Cold Glue

Supple, bituminous, fiberreinforced adhesive for fixing bituminous roof rolls without fire danger or as an adhesive layer for fixing slate chippings or gravel to existing bituminous roof sealing. Forms also a waterproof intermediate layer.

Packing: 5 kg Colour: black







Paraphalt Bitumen

Plasto-elastic sealant reinforced by fibers, for aluina and reparations on bituminous surfaces. Waterproof sealing of joints, rooftop seams, skyliahts, fences, ventilation chimneys, tubes, drainpipes...

Paraphalt Super

Professional adhesive and sealant that adheres to virtually any construction material, including moist surfaces and even under water. It forms a smooth and tight layer whilst remaining flexible.

Paraphalt Butyl

Synthetic rubber-based sealant for indoors and out. Adheres to nearly all surfaces without primer. Can be used on wet surfaces if they are slippery. Seals everywhere in and on the house. For expansion and connection joints.

Packing: 25 x 310 ml & can 6 kg Colour: black Packing: 25 x 310 ml Colour: black **Packing:** 25 x 310 ml. On demand min. 2560 pc **Colour:** white - grey - black

For more information about these and other products, you can consult our technical data sheets on our website www.dl-chem.com or contact your representative.







Paraphalt Primer

Adhesive layer for the application of roofing or bituminous renovation products. Considerably improves the adhesion between the base surface and the material to be applied. Fixates dusty and absorbent surfaces. Drying time: +/- 3 h

Packing: 5 kg & 10 kg Colour: black

Paraphalt High Tack

Modified, bituminous adhesive paste. Permanently elastic. For gluing in dots or stripes of PU insulation material or bituminous roof rolls without burnaway foil on old membranes.

Packing: 15 kg On demand Colour: black

Paraphalt Flex Seal

Paraphalt Flex Seal is a universal, waterproofing adhesive sealant and seamless coating for a wide range of projects and nearly all surfaces. Furthermore it is an environmentally safe product.

Packing: 1 kg, 5 kg & 10 kg **Colour:** black after curing





Parasilico EPDM*

Neutral silicone sealant suitable for the bonding, finishing and sealing of EPDM*. Has an adhesive strength on the majority of materials such as concrete, bricks, aluminium, steel...

*Due to the wide variety of EPDM sheets available a preliminary compatibility test is necessary.

Packing: 25 x 310 ml & 20 x 600 ml **Colour:** black

Paraband BT

air-Verv strong, and watertight, cold gluing seal band based on butyl and alu. Is used between parts of heavy constructions curtain walls and or heavy constructions. Also appropriate for chimney coating, roof-combs, and porches.

Packing: 50, 75, 100, 150, 200, 300 - 0,6 mm x 10 m



	ç					al	lue			8	
	Bitumen	Super	Butyl	Liquid	Reflex	Flex Seal	Cold Glue	Primer	Parafix	Parasilico EPDM*	
	, 	I	1		PHALT	1	I	I	OTH	<u> </u>	
Based on											
Bitumen											
Elastomers											
Fibres											
Adhesion additives											
Acrylates											
Butyl											
Silicones											
Application											
Pre-treatment											
Gluing											
Protection/ reparation											
Materials											
Joints & seams											
Joint											
Roof edge											
Chimney											
Water drainage & leakage											
Glass											
Roofings											
Slates											
Bitumen											
EPDM											
Tiles											
Corrugated sheet											
Surfaces											
Humid surface											
Concrete											
Stone/bricks											
Facade stone											
Metals, zinc											
W											
Very suitable		Suitable			Not recommended				Not suitable		

