



**CHARACTERISTICS**

- Primer in order to obtain an ideal adherence of the **PU** and **MS Parquet adhesive**
- Also reinforces floor surfaces on a concrete base
- Easy to use
- Fast drying
- Highly improved adherence

**APPLICATIONS**

- Can be used on porous substrates and tiled floors.

<b>TECHNICAL CHARACTERISTICS</b>	
Colour	Transparent
Odour	Solvent
Density	Circa 0,9 g/ml
Consumption	70 -1 20 g/m <sup>2</sup>
Drying time	+/- 30 min.
Shelf life, in the original closed packing in a dry, cool place free of frost.	Min. 12 months

<b>PACKING</b>
Can of 5 l - 108 cans/pallet

**METHOD OF USE**

**Application**

- Apply the primer in 1 layer with a roll or brush
- The primer must be completely dry before you apply the parquet adhesive
- Dry time is approximately 30 minutes, depending on the circumstances
- The primer reacts with the humidity. Therefore the pot must be closed carefully after use

**Cleaning**

With acetone or MEK.

**SAFETY**

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.